



Data sheet

CP-TR14-16330

CompactPCI board level product

Your partner in automation

Galvanic isolated 16 channel transient recorder / ADC module

Features

- 16 channels
- Simultaneous sampling
- 100 kHz bandwidth
- Max. 200 kS/s per channel
- Direct readout and/or transient recorder function
- Input range +/- 10 Volt
- 16 bit resolution
- Differential input
- Common mode range +/- 270 Volt, each channel
- Input protection +/- 500 Volt, each channel
- Galvanic isolation
- 16 MSample of onboard memory per channel
- Samples also available via FIFO's
- Selectable trigger options, including on the analog inputs
- Pre and post trigger recording with actual time counters
- PCI Specification version 2.2, 32-bit, 33-MHz
- 6U, single slot CompactPCI form factor



Description

The TR14 module is a galvanic isolated 16 channel digitizer with onboard memory in a 6U high CompactPCI form factor. The 16 channels are sampled simultaneously with 16 bit resolution. The samples are stored in onboard memory. The memory is organized as a ring buffer. On every sample clock the A to D converters convert the analog inputs and send the samples over the isolation barrier where they are stored into the ring buffer. After the event of a trigger a programmable number of post trigger samples will be stored into this ring buffer before sampling stops. The number of samples from start until trigger is counted in 32 bit counters. The samples in memory can be copied over the CompactPCI bus with DMA transfers. In parallel samples are also available through FIFO's at sub sample rates for control applications. The depth of the FIFO's is software selectable, up to 16 samples per channel.

Modules may be connected via the front panel trigger- and clock signals or via PXI to increase the number of channels.

The plug and play functionality provides easy setup and use. The module includes software drivers for Linux.



Design and manufacturing of computer systems for industry, science and OEM



Data sheet

CP-TR14-16330

CompactPCI board level product

Your partner in automation

Technical Specifications

INPUT

- Number of inputs : 16
- Input type : differential
- Input range : +/- 10 Volt, other ranges on request
- Full power bandwidth : 100 kHz
- Small signal bandwidth : 100 kHz
- Full scale step response overshoot : < 10 %
- Differential input impedance : typ. 800 kOhm
- Common mode rejection : > 80 dB @ 50 Hz
- Common mode range : +/- 270 Volt
- Damage limit : +/- 500 Volt differential or common mode
- Input connector : 37 pole D-connector, female. JET standard pin out YA-A009-0436

TRANSFER CHARACTERISTICS

- Sample rate : max 200 kS/s per channel
- Resolution : 16 bits
- No missing codes : typ. 16 bits, min. 15 bits
- INL : typ. +/- 1 LSB max. +/- 3 LSB
- DNL : typ. 0.5 LSB, min. -2 LSB, max. +3 LSB
- SNR : > 80 dB @ 10 kHz full scale
- THD : < -70 dB @ 10 kHz full scale
- Gain error : < 0.05% of full scale range over operating temperature range
- Offset error : ≤ 3 LSB over operating temperature range
- Cross talk between channels : < -80 dB

MEMORY

- Record length : max. 16 MS per channel
- FIFO depth : max 16 samples per channel
- Number of FIFO's : 16, one for each channel

DMA

- DMA transfer rate : > 100 Mbyte/s sustained
2 samples per 32 bit word

Design and manufacturing of computer systems for industry, science and OEM



Data sheet

CP-TR14-16330

CompactPCI board level product

Your partner in automation

SAMPLE CLOCK

- Source : internal or external (front or PXI)
- Sample rate internal clock : 200 kS/s divided by 1 to 65535, programmable
- Internal sample clock stability : 50 ppm over operating temperature range.
- Sample clock input : TTL, 50 Ohm termination selectable, edge selectable
- Sample clock output : TTL, short circuit protected, 50 Ohm driving capability
- Sample clock connectors : 2 x LEMO 00

TRIGGER

- Source : internal, on analog input signal or external (front or PXI)
- Trigger input : TTL, 50 Ohm termination selectable, edge selectable
- Trigger output : TTL, short circuit protected, 50 Ohm driving capability
- Trigger connectors : 2 x LEMO 00

ISOLATION

- Isolation barrier : > 200 V working voltage (RMS or DC)
> 1500 V RMS 50/60 Hz, 1 min.
- Signal transfer : capacitive couplers
- Power transfer : DC/DC converters, no external power required

MECHANICAL

- Height : 6U
- Width : 1 slot

ENVIRONMENTAL CONDITIONS

- Max. operating relative humidity : 90 %, no condensation
- Operating temperature : 15 – 40 °C
- Power supply requirements : + 5 and + 3.3 Volt derived from CompactPCI,
1.5A max (5V), 0.5A max (3.3V)

WARRANTY

: 1 year

ORDERING INFORMATION

- CP-TR14-16330 : 29-16330-0

Design and manufacturing of computer systems for industry, science and OEM