



**Data sheet**

**SP-ISBP6-XXXXX**

**Industrial PC systems**

**Your partner in automation**

## **Ruggedized Industrial Small Box PC**

High-performance industrial Small Box PC featuring Intel's 4th-gen Core Haswell (LGA1150) desktop CPUs.



### **Features**

- Ruggedized stainless steel housing with powder coating
- 4th Generation Intel® Core i7 / i5 / i3 / Pentium Processor. Intel Q87 Chipset
- Long-Life Embedded Class with Planned Lifecycle Through Q4'2018
- Intel HD 4000/5000 Graphics, DirectX 11.1
- Support up to Three Independent Displays, HDMI, DVI, VGA, 24bit LVDS
- ECO-design for EuP/ErP
- Supports DDR3-1600 SODIMM up to 16GB Total
- 1 \* Shared mSATA/mini-PCI Express Slot
- Dual Intel Gigabit LAN, Intel iAMT 9.0 Supported 2x SATA, 8x USB 2.0, 4x COM, Watchdog timer

***Design and manufacturing of computer systems for industry, science and OEM***



## Data sheet

### SP-ISBP6-XXXXX

Industrial PC systems

Your partner in automation

## Description

The SP-ISBPX is based on the NF9J-Q87 Mini-ITX Motherboard with the 4th Generation Intel® Core i7 / i5 / i3 / Pentium Processor Socket LGA 1150 (Formerly Haswell). This board is compatible with Win XP, Win 7, Win 8 and Linux. The ISBP can be powered with a power supply from 9VDC up to 36VDC. This makes the ISBP suitable for automotive applications. The fans (CPU, Case) are Temperature controlled.


## Technical Specifications of the Motherboard

- Model / Series :NF9J
- Part No :JNF9J-Q87
- Processor :Socket LGA1150, Supports 4th Generation Intel Core i3, i5, i7 Processors (Haswell)
- Chipset :Intel Q87 Express Chipset
- Video :Intel HD 4000/5000 Graphics in processor, DirectX 11.1, OpenGL 4.0
- Memory :2 \* 204-pin SO-DIMM slots supporting dual channel DDR3-1600 :up to 16GB total
- Expansion Slots :1 \* PCI Express 3.0 x16 Slot
- Storage :5 \* SATA3 6Gb/s ports supporting RAID 0, 1, 5, 10, JBOD :1 \* Shared mSATA/mini-PCI Express slot (Full-size)
- Audio :Realtek ALC662 5.1 Channel HD Audio
- Network :1 \* Intel i211AT Gigabit LAN, 1 \* Intel i217LM Gigabit LAN with iAMT 9.0 support
- Other Features :Support ACPI S3, CPU Smart FAN, Watchdog Timer 10-255 :min/sec
- Rear Panel I/O :2 \* USB 3.0 Ports :4 \* USB 2.0 Ports :2 \* RJ-45 Ports :2 \* Serial Ports (1 \* RS232, 1 \* RS232/422/485) :1 \* HDMI, 1 \* DVI-D, 1 \* VGA :3 \* Audio Jacks (Line In, Line Out, Mic In)
- Internal I/O :1 \* USB Header for 2 \* USB 3.0 Ports :2 \* USB Headers for 4 \* USB 2.0 Ports :CPU Fan connector, 2 \* SYSFAN connectors :1 \* PS/2 Mouse/Keyboard connector :2 \* Serial Port Headers (1 \* RS232, 1 \* RS232/422/485) :8-bit GPIO Header, CIR Header, Chassis Intrusion Header :24-pin ATX and 4-pin 12V\_ATX Power connectors
- BIOS :AMI UEFI 64MB DIP Flash ROM
- Certification :CE, FCC, RoHS, ErP
- Temperature :Operating Temperature 0~60 ° C, Storage Temp -20-85 ° C

## Mechanical Dimensions

- Height :215 mm
- Width :85 mm
- Length :230 mm

***Design and manufacturing of computer systems for industry, science and OEM***



## ***Data sheet***

### **SP-ISBP6-XXXXX**

**Industrial PC systems**

**Your partner in automation**

#### **Environmental Conditions**

- Max. operating relative humidity :90 %, no condensation
- Operating temperature :0 – 60 °C
- Power supply requirements :9V – 36V / DC / 40W

**Warranty** :1 year

#### **Ordering Information**

- SP-SBP6-17753 :29-17753-6  
Intel Core i3-4130T 2,9GHz, 35W  
mSata SSD 64GB  
16GB RAM
- SP-SBP6-XXXXX :Other configurations on request

***Design and manufacturing of computer systems for industry, science and OEM***